

metalfire

| architectural fireplaces |

model **UNIQUE MF 1050-75 GHE 1S**

Dimensions (mm)

- combustion opening WxH 1060 x 789
- glass door WxH 1050 x 754
- length of burner 650
- external WxDxH 1160 x 429 x 1128
- flue connection Ø130/Ø200 or
(*) Ø100/Ø150

Technical Data (city gas)

- appliance type C11/C31/C31S
- load 11,5 kW
- type of gas/pressure G20/G25
20/25mBar
- gascat. I2E+, I2H, I2E, I2L
- weight (woodlogs &
options not included) 160kg

Specifications

- only available with ceramic wood logs
- ionization-protected pilot-flame
- control unit in the middle,
below the combustion chamber
- finishing: heat-resistant black paint
- radiographic remote control with
thermostatic mode
- fan for convection air
- gas/electrical connections at the left side
- interior finish: STANDARD (plain steel)


Options

- promat insulation kit
- interior finish: MINIMAL
(plain steel 20 cm wide stripes with 2 x 2 cm joints)
- interior finish: ORIGINAL (ribbed cast iron)
- interior finish: DESIGN (random steel strips)

(*) according to flue configuration (see manual)

scale 1:20

www.metalfire.eu

EN 613 

General dimensional tolerances up to 6mm
Metalfire preserves the right to modify specifications without previous notice

